



Tow 'N Dump

Siebring Manufacturing produces the Tow 'N Dump Aeration Cart specifically with the options requested by the customer to use in their specific application.

The Tow 'N Dump Aeration Cart has the option of a folding rear gate and hydraulic lift or fold down sides and no hydraulic lift. Both carts have a perforated floor and hookups for steam and air equipment.



RUNNING GEAR FEATURES

- Running gear weight tested at 6400 lbs. (dropped 6" abuse)
- 18 x 8.5" wheels (10 mph - non-highway)
- Wheel spindles w/roller bearings

CART SPECIFICATIONS

- Cart capacity of 2 cubic yards
- Aeration cart with 40% aerator floor 4' wide x 8' long w/24" sides
- Dump cart with smooth dump floor 4' wide x 8' long w/24" sides
- Canvas cover for aeration carts

CART OPTIONS

- Aeration cart with fold down sides for work bench / flat filling
- Aeration cart with fold up rear gate and battery powered hydraulic lift with safety locks
- 10 amp - 12 volt battery charger for battery powered hydraulics
- Custom aerator and steam fittings available



The cart with hydraulic lift features an easily operated lift control shown here.



Looking down into the cart shows the specially designed screen panel that supports the soil while allowing the air to pass through.



Locking support arms allow for safe maintenance of the cart.



GEORGE, IOWA 51237 U.S.A.

PHONE: 888-475-3317
FAX: 712-475-3490
WEB: WWW.SIEBRINGMFG.COM